

CLAIMS

1. (Currently Amended) A method ~~for reading sensor~~, comprising:
scanning an image with a plurality of sensing units;
storing the scanned data associated with the image to a plurality of memory cells;
connecting a linear sensor and receiving a starting parameter to identify at least one of the
N, wherein said linear sensor has a plurality of memory cells storing data associated with the
scanned image arranged in linear order and each said cell is independent from other said cells;
and said parameter N is a positive integer;
numbering said memory cells sequentially from a first memory cell to a (N-1)-th
memory cell depending on the linear arrangement order; and
sequentially reading the data stored in one or more of the contents of the unnumbered
memory cells, beginning with the memory cell identified by the starting parameter sequentially
from the N-th memory cell.
2. (Original) The method of claim 1, wherein said memory cells are each independent from other said cells and are read separately.
3. (Currently Amended) The method of claim 1, wherein said starting parameter is set by manually input when said linear sensor is needed to be read.
4. (Currently Amended) The method of claim 1, wherein starting parameter is automatically generated by said linear sensor.

5. (Currently Amended) The method of claim 1, wherein starting parameter corresponds to a specific memory cell that is the first one of said memory cells stored nonzero signal when said linear sensor is sensing an object.

6. (Currently Amended) ~~The A~~ method comprising: of claim 1;
receiving a parameter N, wherein said linear sensor has a plurality of memory cells
arranged in linear order and each said cell is independent from other said cells, and said
parameter N is a positive integer;
numbering said memory cells sequentially from a first memory cell to a (N-1)-th
memory cell depending on the linear arrangement order; and
reading the contents of the unnumbered memory cells sequentially from the N-th memory
cell, wherein an attached parameter L can also be received at the same time to receive said parameter N, and L is a positive integer larger than N, wherein by way of said attached parameter to stop reading unnumbered memory cells after reading the L-th one of memory cells in the linear arrangement order.

7. (Original) The method of claim 6, wherein said attached parameter is set by manually input when said linear sensor is needed to be read.

8. (Original) The method of claim 6, wherein said attached parameter is one of said parameters of said linear sensor.

9. (Original) The method of claim 6, wherein said attached parameter is a specific memory cell stored the last nonzero signal when said linear sensor is sensing an object.

10. (Currently Amended) A method for reading sensor, comprising:
~~connecting a 2-D sensor and~~ receiving a specific amount of parameters, wherein said 2-D sensor is composed of a specific amount of linear sensors, and each said linear sensor has a plurality of memory cells arranged by linear order and each parameter is a positive integer corresponding to a single linear sensor; and
proceeding the reading action of each said linear sensors from the first one, comprising:
numbering said memory cells sequentially depending on linear arrangement order from said first memory cell until the (N-1)-th memory cell, wherein N is said parameter corresponding to said linear sensor; and
reading the contents of said memory cells that are unnumbered in linear arrangement order sequentially.

11. (Original) The method of claim 10, wherein each said memory cell is independent from other said cells and are read separately.

12. (Original) The method of claim 11, wherein each said parameter is set by manually input when said 2-D sensor is needed to be read.

13. (Original) The method of claim 11, wherein each said parameter is automatically generated by corresponding said linear sensor.

14. (Original) The method of claim 11, wherein each said parameter is a specific memory cell that is the first one of said memory cells stored nonzero signal when corresponding said linear sensor is sensing an object.

15. (Original) The method of claim 11, wherein a plurality of attached parameters can be received at the same time to receive said parameters, wherein each of said attached parameter is an integer larger than corresponding parameter.

16. (Original) The method of claim 15, wherein each of said linear sensors corresponds to a specific one of said parameters, but it is not necessary that each of said linear sensors corresponds to a specific one of said attached parameters.

17. (Original) The method of claim 15, wherein each of a certain specific linear sensor corresponds to a certain specific said attached parameter K, stopping reading said memory cells after reading the K-th one of said memory cells when said linear sensor is reading the contents of said unnumbered memory cells sequentially.

18. (Original) The method of claim 15, wherein the source of any attached parameter comprises: manually input at the moment to read said 2-D sensor, the automatic generation by said linear sensor; and the last specific one of said memory cell stored nonzero signal when said linear sensor is sensing an object.

19. (Currently Amended) A method for reading sensor, comprises:

~~connecting a linear sensor and~~ receiving a plurality of parameters, wherein said linear sensor has a plurality of memory cells arranged in linear order and each said memory cell is independent from others, and each of said parameters is a positive integers;

numbering said memory cells sequentially from a first memory cell of said linear sensor depending on linear arrangement order sequentially to find out a plurality of specific memory cells with numbers equal to said parameters, wherein said specific memory cells are paired off and each pair of said specific memory cells marks a specific memory cell section; and

reading said specific memory cell sections sequentially depending on linear arrangement order.

20. (Original) The method of claim 19, wherein a method of determine the range of said specific memory cell sections when the amount of said parameters is odd, comprises:

choosing the first memory cell of all and a first one of said specific memory cells to be a specific memory cell section and pairing the other specific memory cells off; and

choosing the last one of said specific memory cells and the last memory cell of all to be a specific memory cell section and pairing the other specific memory cells off.

21. (New) The method of claim 1, includes

receiving an ending parameter to identify another one of the memory cells; and

sequentially reading data from one or more of the memory cells, beginning with the memory cell identified by the starting parameter and finishing with the memory cell identified by the ending parameter.

22. (New) The method of claim 21 includes setting the ending parameter according to a manual input.

23. (New) The method of claim 21 where the linear sensor automatically generates the ending parameter.

24. (New) A device comprising:

a linear sensor having a plurality of sensing units, configured in a linear arrangement, to detect at least one object; and

a plurality of memory cells to store the detected data associated with the object and allow sequential access to the stored data according to the linear arrangement of the sensing units and a starting parameter, the starting parameter to identify which memory cell is first in a sequence of memory cells to be read.

25. (New) The device of claim 24 where the memory cells allow sequential access to the stored data according to the linear arrangement of the sensing units, the starting parameter, and an ending parameter, the ending parameter to identify which memory cell is last in the sequence of memory cells to be read.

26. (New) A system comprising:

means for scanning an image with a plurality of sensing units;

means for storing the scanned data associated with the image to a plurality of memory cells;

means for receiving a starting parameter to identify at least one of the memory cells storing data associated with the scanned image; and

means for sequentially reading the data stored in one or more of the memory cells, beginning with the memory cell identified by the starting parameter.

27. (New) The system of claim 26 where the memory cells allow sequential access to the stored data according to the linear arrangement of the sensing units, the starting parameter, and an ending parameter, the ending parameter to identify which memory cell is last in the sequence of memory cells to be read.